


CATEGORY 6 U/UTP 26 AWG PATCH CORD



Product Overview

AGER CAT6 U/UTP Patch Cord products feature standard LSOH jackets and comply with ANSI/TIA/568-2-E and ISO/IEC-11801 (2nd edition) standards. They are available in different colours and in the required lengths.

Supported Protocols

- 10BASE-T Ethernet
- 100BASE-T2
- 100BASE-T4
- 100BASE-TX
- 100BASE-T "Fast Ethernet"
- 1000BASE-T Gigabit Ethernet
- ATM 52
- ATM 25
- ATM 155
- TP-PMD
- Token Ring 100 Mbps
- Token Ring 4 Mbps and 16 Mbps
- Broadband and Baseband Video
- ISDN Basic and Primary Access
- 1BASE-5 Starlan
- ISALAN
- ITU V.21 and X.11
- UL94 V-0

Product Shipping Information

PRODUCT SHIPPING INFORMATION	
Product Code	Product Description
ACPC6-600-LA50-GR	4x2x26# U/UTP CAT 6 LSOH Patch Cord Gri 0,50 mt
ACPC6-600-LB1-GR	4x2x26# U/UTP CAT 6 LSOH Patch Cord Gri 1mt
ACPC6-600-LB2-BL	4x2x26# U/UTP CAT 6 LSOH Patch Cord Mavi 2mt
ACPC6-600-LB3-YL	4x2x26# U/UTP CAT 6 LSOH Patch Cord Sarı 3mt
ACPC6-600-LB5-RD	4x2x26# U/UTP CAT 6 LSOH Patch Cord Kırmızı 5 mt

Cable Specifications

MECHANICAL AND PHYSICAL PROPERTIES	
CONDUCTOR	26 AWG cross-section Flexible multi-strand copper 7 x 0.145 mm
CONDUCTOR WIRE COLOURS	Blue x Blue-White, Orange x -WhiteOrange-White, Green x Green-White, Brown x Brown-White
CONDUCTOR WIRE INSULATION	Polyolefin
NUMBER OF WIRES	8 WIRES, 4 PAIRS (twisted)
TAPE COVERING	NONE
FOIL	NONE

CATEGORY 6 U/UTP 26 AWG PATCH CORD

Cable Specifications

MECHANICAL AND PHYSICAL PROPERTIES	
OUTER SHEATH	LSOH (LSZH) Low Smoke Halogen Free
OUTER SHEATH COLOUR	Grey RAL 7035 (Other colours available upon request.)
EARTHING	N/A
BETWEEN PINS	N/A
CABLE MARKING INFORMATION	Brand, Product Code, Cable Type, Relevant Standard, Length, Batch Number
CABLE DIAMETER	4.8 mm $\pm$ 0.3 mm
OPERATING TEMPERATURE	-20 to +60 °C
STORAGE TEMPERATURE	-20, +80°C
TENSILE STRENGTH	10 N
PLUG CABLE TENSILE STRENGTH	90 N
PLUG CONTACT MATERIAL	2.54µm (100µ-inch) Nickel over 1.27µm (50µ-inch) gold plating
DURABILITY	750 times
BENDING RADIUS (Short Term)	8 x Cable Diameter (mm)
BENDING RADIUS (Long Term)	4 x Cable Diameter (mm)
FLAME TEST	IEC 60332-1
CONDUCTIVITY TEST	UL 444

Electrical Transmission Properties

ELECTRICAL TRANSMISSION PROPERTIES	
INSULATION RESISTANCE	500 MegaOhm•Km min. @ 500 Vdc
DC RESISTANCE	95 Ohm/km
RESISTANCE UNBALANCE	%2 Maks.
VOLTAGE	72 Vdc max
DIELECTRIC STRENGTH	1000 Volts AC / 1 Minute
CURRENT	1.5 A MAX.
SIGNAL TRANSMISSION TIME (Prob. Delay)	2.5 nS Maks @ 1-250 MHz
INTER-PERL SIGNAL DELAY (Scew Delay)	1.25 nS Maks @ 1-250 MHz